





## Spannweiten

| Belastbarkeit<br>kg/m <sup>2</sup> | Material<br>Stärke<br>mm. | Max. Spannweite / m  |  |  |  | Max. Spannweite / m   |   |   |   |
|------------------------------------|---------------------------|--|--|--|--|---|---|---|---|
|                                    |                           |  |  |  |  |  |  |  |  |
|                                    | Behältnis                 | L/150  | L/200  | L/250  | L/300  | L/150   | L/200   | L/250   | L/300   |
| 100                                | 40                        | 3,29   | 2,99   | 2,77   | 2,60   | 3,53  | 3,53  | 3,53  | 3,50  |
|                                    | 60                        | 4,08   | 3,71   | 3,44   | 3,24   | 4,09  | 4,09  | 4,09  | 4,09  |
|                                    | 80                        | 4,61   | 4,38   | 4,07   | 3,83   | 4,61  | 4,61  | 4,61  | 4,61  |
|                                    | 100                       | 5,01   | 4,78   | 4,47   | 4,13   | 5,01  | 5,01  | 5,01  | 5,01  |
| 120                                | 40                        | 3,09   | 2,81   | 2,60   | 2,45   | 3,22  | 3,22  | 3,22  | 3,22  |
|                                    | 60                        | 3,73   | 3,49   | 3,24   | 3,05   | 3,73  | 3,73  | 3,73  | 3,73  |
|                                    | 80                        | 4,20   | 4,13   | 3,83   | 3,60   | 4,20  | 4,20  | 4,20  | 4,20  |
|                                    | 100                       | 4,60   | 4,53   | 4,23   | 4,00   | 4,60  | 4,60  | 4,60  | 4,60  |
| 140                                | 40                        | 2,93   | 2,67   | 2,48   | 2,33   | 2,98  | 2,98  | 2,98  | 2,98  |
|                                    | 60                        | 3,45   | 3,32   | 3,08   | 2,90   | 3,45  | 3,45  | 3,45  | 3,45  |
|                                    | 80                        | 3,89   | 3,89   | 3,64   | 3,42   | 3,89  | 3,89  | 3,89  | 3,89  |
|                                    | 100                       | 4,29   | 4,29   | 4,04   | 3,82   | 4,29  | 4,29  | 4,29  | 4,29  |

## Eigenschaften

| Material<br>Stärke<br>mm | Gewicht<br>kg/m <sup>2</sup> | U - Wert<br>W/m <sup>2</sup> ·K | R - Wert<br>m <sup>2</sup> ·K/W | Max.<br>Belastbarkeit<br>kg·m |
|--------------------------|------------------------------|---------------------------------|---------------------------------|-------------------------------|
| 40                       | 11,71                        | 0,52                            | 1,92                            | 276                           |
| 60                       | 12,51                        | 0,38                            | 2,77                            | 371                           |
| 80                       | 13,30                        | 0,29                            | 3,62                            | 471                           |
| 100                      | 14,10                        | 0,23                            | 4,48                            | 568                           |